


WAFER PRODUCT DATASHEET (ADDENDUM)

Product	AT25DF021A-DWF and AT25DF021A-DWFHT																																								
Description	2Mbit, Fusion, 1.65V – 3.6V VCC																																								
Die Map	 <p>Image reflects relative pad positioning only; not representative of actual die</p> <p>Wafer relative to die orientation (ref die coordinates table)</p>																																								
Die Size & Pad Coordinates	<table border="1"> <thead> <tr> <th></th> <th>X (μm)</th> <th>Y (μm)</th> </tr> </thead> <tbody> <tr> <td>Die Size</td> <td>1540</td> <td>1320</td> </tr> <tr> <td>Scribe Line Width</td> <td>80</td> <td>80</td> </tr> <tr> <td>Die Step</td> <td>1620</td> <td>1400</td> </tr> <tr> <td>Pad Opening</td> <td>65</td> <td>65</td> </tr> <tr> <td>CSB</td> <td>-691.5</td> <td>92.85</td> </tr> <tr> <td>SO</td> <td>-691.5</td> <td>-124.8</td> </tr> <tr> <td>WPB</td> <td>-691.5</td> <td>-351.99</td> </tr> <tr> <td>GND</td> <td>-691.5</td> <td>-496.99</td> </tr> <tr> <td>SI</td> <td>692.5</td> <td>-450.29</td> </tr> <tr> <td>SCK</td> <td>692.5</td> <td>-223.1</td> </tr> <tr> <td>HOLDB</td> <td>692.5</td> <td>-79.29</td> </tr> <tr> <td>VCC</td> <td>692.5</td> <td>58.78</td> </tr> </tbody> </table>			X (μm)	Y (μm)	Die Size	1540	1320	Scribe Line Width	80	80	Die Step	1620	1400	Pad Opening	65	65	CSB	-691.5	92.85	SO	-691.5	-124.8	WPB	-691.5	-351.99	GND	-691.5	-496.99	SI	692.5	-450.29	SCK	692.5	-223.1	HOLDB	692.5	-79.29	VCC	692.5	58.78
	X (μm)	Y (μm)																																							
Die Size	1540	1320																																							
Scribe Line Width	80	80																																							
Die Step	1620	1400																																							
Pad Opening	65	65																																							
CSB	-691.5	92.85																																							
SO	-691.5	-124.8																																							
WPB	-691.5	-351.99																																							
GND	-691.5	-496.99																																							
SI	692.5	-450.29																																							
SCK	692.5	-223.1																																							
HOLDB	692.5	-79.29																																							
VCC	692.5	58.78																																							

Technical Details	
Adesto Product Family	Fusion
Density	2 Mbit
Operating Vcc	1.65V - 3.6V
ESD	>2kV JESD22-A114
Delivery Option	Wafer- unsawn
Wafer Size (mm)	200
Process Geometry (nm)	110
Die ID	63754
Wafer Map	Electronic- text file
Manufacturing Facility	UMC
Wafer Thickness (µm) Maximum	725
Back Grind Options	None / Contact Adesto
Back Plane Connection	Floating / Not Required
Backside preparation / metallization	None
Bond wire qualified	AU <input checked="" type="checkbox"/> CU <input type="checkbox"/> AG <input type="checkbox"/>
Passivation Material	HDP oxide + SiON
Passivation Thickness (Å)	21000
Bond Pad Material	Ti/TiN/AlCu
Bond Pad Thickness (Å)	6000
Good Die per Wafer	Contact Adesto (AT25DF021A-DWF) ¹
Good Die per Wafer	Contact Adesto (AT25DF021A-DWFHT) ¹
Active Circuits underneath the bond pad	Yes

¹ Average value; subject to change without notice.

Part Number Ordering Code ²	Operating Temperature Range	Functional Specification
AT25DF021A-DWF	-40°C to 85°C	http://www.adestotech.com/wp-content/uploads/DS-AT25DF021A-042.pdf
AT25DF021A-DWFHT	-40°C to 125°C	http://www.adestotech.com/wp-content/uploads/DS-AT25DF021A-HRADD.pdf

Adesto Technologies Corporation

1250 Borregas Avenue, Sunnyvale, CA 94089 | phone: (408)400-0578 fax: (408) 400-0721 | www.adestotech.com

©2015 Adesto Technologies. All rights reserved. Adesto, the Adesto logo & CBRAM are trademarks of Adesto Technologies Corporation.

² Handle product in accordance with UV and ESD precautions.

Revision Level – Release Date	History
A – August 2015	Initial release.
B – November 2015	Updated wafer orientation in die map image. Added footnote on handling.

Disclaimer: Adesto Technologies Corporation makes no warranty for the use of its products, other than those expressly contained in the Company's standard warranty which is detailed in Adesto's Terms and Conditions located on the Company's web site. The Company assumes no responsibility for any errors which may appear in this document, reserves the right to change devices or specifications detailed herein at any time without notice, and does not make any commitment to update the information contained herein. No licenses to patents or other intellectual property of Adesto are granted by the Company in connection with the sale of Adesto products, expressly or by implication. Adesto's products are not authorized for use as critical components in life support devices or systems.